## GEOPHYSICAL MODEL OF TIN SKARN AND RELATED DEPOSITS

COX AND SINGER combined models; 14b, tin skarn; Compilers- D.B. Hoover 14c, replacement tin; 15b, tin veins; D.H. Knepper 15c, tin greisens; and tin pegmatites-(no geological model yet)

Geophysically related models; 20a, porphyry tin; 20b, tin-polymetallic, 25b rhyolitic tin; 39e, placer tin

A. Geologic Setting

ŽPegmatite, greisen, vein, skarn, replacement, and fissure lodes developed within or external to specialized leucogranites.

ŽGenerally associated with apical parts of the specialized leucogranites.

ŽPlutons are generally of S or A type, ilmenite series granitoids

B. Geologic Environment Definition

(Hosking, 1988)

Geophysics is used primarily to define permissive areas where leucocratic source granites are present, especially highly differentiated, late stage phases of these source granites.

Magnetic response of parent granitoid weak to non existent, typical of S or A type, ilmenite series granites. Where skarn, replacement, or vein mineralization is present in host rock an irregular magnetic haloe may be present (Bishop and Lewis, 1988; Asanov, 1978; Xianguang, 1988; Webster, 1984a).

Parent granitoid generally shows as a gravity low due to typical  $0.1 \, \text{gm/cm}^3$  density contrast (Asanov, 1978; Gongjian and Rui, 1988; Bishop and Lewis, 1988).

Radioelement content of parent granitoid is high to very high, giving definition by airborne methods where exposed. High uranium (Yeates and others, 1982) or high thorium (Chatterjee and Muecke, 1980; Towsey and Patterson, 1984) often are keys to enriched parts of pluton.

Electrical techniques are used to map the upper surface of buried plutons to locate apices (Alonso and Corral, 1983; Xianguang, 1988).

Exposed parts of felsic plutons may have distinctive remote sensing signatures, and separate intrusive phases may be identified (Amaral, 1982; Keighley and others, 1980, Guerra, 1978, Moore and Carom, 1983). Covered tin granites have been identified from Landsat data (Marconnet, 1984). Tin granites have been reported confined to areas of relatively shallow depths to the Mohorovicic discontinuity (Gongjian and Rui, 1988), but Zeitz and others (1976) note that in southeast Russia tin is related to a thick crust.

# c. Deposit Definition

Geophysical expression is variable, in part due to different deposit types covered. Magnetic and electrical methods are most often applied because of presence of pyrhotite, and accessory sulfides present in ore, giving rise to local magnetic, resistivity and IP anomalies. Locally, elevated Radioelement content may identify favorable structure, especially where latestate alteration has decreased potassium content (Towsey and Patterson, 1984). Gravity may reveal local highs related to metamorphism of surrounding host (Asanov, 1978; Rulski, 1982).

D.	Size and Shape of	Shape	Average Size/Range
	apices of pluton	irregular blister to vertical cylinder	0.25 - 2 km diam.
	deposit	variable, irregular tabular	skarn, replacement 2.6x10°m³ greisen .3x10°-24x10°m³ vein 8.9x10⁴m³
	alteration haloe	donut shape around apices, irregular around deposit	may extend to several kms from pluton

Ε.	Physical Properties (units)	Deposit	Alteration	Source Granitoid	Host
				Leucocratic Granitoid	
1.	Density (gm/cm3)	3.9 <sup>(26)</sup> ; 2.52-2.84 <sup>(22)</sup> Ao=0.10 <sup>3</sup>	2.8 <sup>(26)</sup> 2.673	low, $_{2.55}^{(3)}$ ; $_{2.54-2.68}^{(22)}$	*
2.	Porosity	variable	variable	variable-low	*
3.	Susceptibility S.I.x10 <sup>-3</sup>	variable, low to moderate, 6.43 (22)	variable	low, 6-87 <sup>(22)</sup>	*
4.	Remanence	?	?	?	*
5.	Resistivity (ohm-m )	$10'  \text{s} - 100^{(26)} \\ 2000 - 6000^{(3)} \\ 17 - 30K^{(22)}$	2000-8000(26)	high-very high 400-1900 (26) 26-56K (22)	*
6.	IP Effect %	5-12 <sup>(9)</sup> 8-12 <sup>(3)</sup>	moderate	low	*
7.	Seismic Velocity (km/sec )	P-2.7-4.1 <sup>(22)</sup> S-1.1-2.6 <sup>(22)</sup>	high?	high P-4.6-6.3 <sup>(22)</sup> S-2.8-4.0 <sup>(22)</sup>	*
e.	Radioelements				
	K (%)	variable, high or low	?	moderate to high	*
	U (ppm) Th (ppm)	high? variable, high to low	must be $>4^{(25)}$ >6 (7)	moderate to high moderate to high	
9.	Other				
	self-potential	moderate to high	?	low-very low	*

# F. Remote Sensing Characteristics

Tin-bearing-ore minerals are not spectrally distinctive in the visible and near-infrared parts of the spectrum. Remote sensing expression is based on indirect indicators including spectral, albedo, and textural differences between granitic parent rocks, the contact metamorphic aureole, and the country rocks (James and Moore, 1985; Keighley and others, 1980), vegetation differences between granitic parent rocks and the country rocks (Moore and Carom, 1982), and structural features mappable on various types of images and photos (James and Moore, 1985). Hydroxyl-bearing alteration minerals (clays, micas), iron oxides, and carbonate host rocks can be uniquely identified with high-spectral resolution instruments in the visible and near-infrared (Rowan and others, 1983; Clark and others, 1990), and broad-band data in the visible and near-infrared, such as Landsat Thematic Mapper, are effective for separating the clay-carbonate and iron oxide mineral groups from unaltered, non-iron oxide bearing and non-carbonate parent and country rocks (Knepper, 1989).

#### G. Comments

A distinct gravity low, to several 10's of mgal, and magnetic low surrounded by an annular ring of local magnetic highs often is a key to presence of source granite and mineralization in surrounding host. The high resistivities of source granites and metamorphosed host give good penetration by EM methods. AEM methods may be particularly effective in this environment. The Radioelement pattern is apt to be complex due to late stage metasomatism that may produce local K and Th depletion. Passing mention in the literature is made to piezoeiectric methods for tin vein deposits.

## H. References

- 1. Alonso, F.F., and Corral, F.J. Gonzalo, 1983, Aplicacion de metados geofisicos en prospeccion de recursos naturales en la zona centro de la Provincia de Salamanca (application of geophysical methods in prospecting for natural resources in the central zone of Salamanca Province [Spain], in Reunion de Xeoloxia e Mineria do Noroeste Peninsular (Novembro 1982) Cuadernos do Laboratorio Xeoloxico de Laxe, no. 6, p. 471-494.
- Amaral, Gilberto, 1982, Automatic interpretation of Landsat imagery for mineral exploration in the Amazon region, <u>in</u> Laming, D.J.C., and Gibbs, A.K., eds., Hidden Wealth: Mineral Exploration Techniques in Tropical Forest Areas, Assoc. of geoscientists for International Development Report No. 7, p. 149-154.
- Asanov, S.I., 1978, Possibilities of using geophysical methods in prospecting for tin in the northern Maritime territory: Soviet Geology and Geophysics, v. 19, no. 2, Allerton Press translation, p. 73-79.
   Bishop, J.R., and Lewis, R.J.G., 1988, The application of geophysics on
- 4. Bishop, J.R., and Lewis, R.J.G., 1988, The application of geophysics on the west coast of Tasmania: Exploration Geophysics, v. 19, no. 1/2, p. 235-236.
- 5. Blaha V., Ferenc, P., and Kusak, B., 1975, Postavenie geofyziky v metodike vyhl'adávania cinonsnývh granitových intruzii v Spišsko-gemerskom rudohori (The role of geophysics in prospecting for tin-bearing granite intrusions in the Spis-Gemes) Geologický pruzkum, v. 17, no. 8, p. 229-232 (in Czech).
- 6. Bureau of Mineral Resources, 1982, Tasmanian tin and tungsten granites— Their radiometric characteristics: Australian Bureau of Mineral Resources BMR 81, yearbook, p. 19-20.
- 7. Chatterjee, A.L., and Muecke, G.K., 1982, Geochemistry and the distribution of uranium and thorium in the granitoid rocks of the South Mountain batholith, Nova Scotia: some genetic and exploration implications, in Maurice, Y.T., ed., Uranium in Granites: Geological Survey Canada Paper 81-23, p. 11-17.
- 8. Clark, R.N., Gallagher, A.J., and Swayze, G.A., 1990, Material absorption band depth mapping of imaging spectrometer data using a complete band shape least-squares fit with library reference spectra: Proceedings of the Second Airborne Visible/Infrared Imaging Spectrometer (AVIRIS) Workshop, JPL Publication 90-54, p. 176-186.
- 9. Gongjian, Wu and Rui, Gao, 1988, Some results and prospects in the application of geophysical and geochemical methods to the search for tin deposits, <u>in</u> Geology of Tin Deposits, Hutchison, C.S., ed.: Springer-Verlag, p. 293-305.
- 10. Guerra, S.M.S., 1978, Notas previas do Projecto Rondonia (preliminary notes of Project Rondonia): Anais de xxx Congresso Brasileiro de Geologia, v. 1, p. 139-146.

- 11. Hosking, K.F.G., 1988, The world's major types of tin deposit, in Hutchison, C.S., ed., Geology of Tin Deposits in Asia and the Pacific: Springer Verlag, p. 3-49.
- 12. Isles, D.J., Limb, N.J., Asten, M.W., and Clarke, D.A., 1984, Geophysical techniques for exploring the basalt covered region in northwestern Tasmania, in Mineral Exploration and Tectonic Processes in Tasmania, Burnie, Tasmania: Geol. Soc. Australia, p. 36.
- 13. James, J.M., and Moore, J.M., 1985, Multi-seasonal imagery studies for geological mapping and prospecting in cultivated terrain of S.W. England, Proceedings of the International Symposium on Remote Sensing of Environment: Fourth Thematic Conference, Environmental Research Institute of Michigan, v. 1, p. 475-484.
- 14. Keighley, J.R., Lynn, W.W., and Nelson, K.R., 1980, Use of Landsat images in tin exploration, Brazil, <u>in</u> Proceedings of the Fourteenth International Symposium on Remote Sensing of Environment:
- 15. Knepper, D.H., Jr., 1989, Mapping hydrothermal alteration with Landsat Thematic Mapper data, <u>in</u> Lee, Keenan, ed., Remote sensing in exploration geology—A combined short course and field trip: 28th International Geological Congress Guidebook T182, p. 13-21, Environmental Research Institute of Michigan, v. 2, p. 341-343.
- Institute of Michigan, v. 2, p. 341-343.

  16. Lericolais, G., Berna, S., Hamza, Y., Lallies, S., Mulyadi, W., Robach, F. and Sujitno, S., 1987, High-resolution seismic and magnetic exploration for two deposits in Bangka, Indonesia: Marine Mining, v. 6, p. 9-21.
- 17. Marconnet, Bendit, 1984, Méallogénie-utilisation de la télédétection spatiale pour la prospection minière d'indices lies à des apex leucogranitiques non affleurants (Metallogenesis-use of remote sensing for ore deposit prospection in relation to non-outcropping leucogranitic apices): Comptes Rendus, Acad. Sci., Paris, T. 298, série II, no. 6, pp. 215-218.
- 18. Moore, J.M., and Carom, Simon, 1982, Interactive enhancement of Landsat imagery for structural mapping in tin-tungsten prospecting--A case history of the S.W. England orefield (U.K.), in Proceedings of the International Symposium on Remote Sensing of Environment: Second Thematic Conference Environmental Research Institute of Michigan, v. 11, p. 727-740.
- 19. Rowan, L.C., Goetz, A.F.H., Crowley, J.K., and Kingston, M.J., 1983, Identification of hydrothermal mineralization in Baja California, Mexico, from orbit using the shuttle multispectral infrared radiometer: IEEE Digest, v. 1, p. 3.1-3.9.
- 20. Rulski, Stefan, 1982, Rola i miejsce bodan geofizycznych przy poszukiwaniu i rozpoznawaniu zloz rud cyny (role and place of geophysics in research and exploration of tin ores): Przeglad Geologiczny, no. 8, p. 413-423, (in Polish with English summary)
- 21. Towsey, C.A.J., and Patterson, D.J., 1984, Tin exploration at Mount Isa--A case history: Journal of Geochemical exploration, v. 22, p. 71-82.
- 22. Verkeijen, P.J.T., Ademiluyi, R.A., and Ajakaiye, D.E., 1982, Geophysical exploration of the Ririwai tin lode in a tropical terrain--A case history, in Laming, D.J.C., and Gibbs, A.K., eds., Hidden Wealth: Mineral Exploration Techniques in Tropical Forest Areas, Association of geoscientists for International Development, p. 136-141.
- 23. Webster, S.S., 1981, Geophysical response of tin granites in central NSW: Bull. Aust. Sot. Explor. Geophys., v. 12, no. 3, p. 63.
- 24. Webster, S.S., 1984a, A magnetic signature for tin deposits in south-east Australia: Exploration Geophysics, v. 15, no. 1, p. 15-31.

- 25. Webster, S.S., 1984b, Comments on the use of gamma-ray spectrometry for tin prospecting: Exploration Geophysics, v. 15, no. 1, p. 61-63.
- 26. Xianguang, Cao, 1988, Integrated geophysical and geochemical indicators of the Gejiu [Kochiu] tin mine and its neighboring areas, <u>in</u> Geology of Tin Deposits, Hutchinson, C.S., ed.: Springer Verlag, p. 443-455.
- 27. Yeates, A.N., Wyatt, B.W., and Tucker, D.H., 1982, Application of gamma-ray spectrometry to prospecting for tin and tungsten granites, particularly within the Lachlan Fold belt, New South Wales: Economic Geology, v. 77, p. 1725-1738.
- 28. Zeitz, Isidore, Eaton, G.P., Frischknecht, F.C., Kane, M.F., and Moss, C.K., 1976, A western view of mining geophysics in the U.S.S.R.: Geophysics, v. 41, no. 2, p. 310-323.




Figure A. Simplified diagram showing distribution of rock density, susceptibility, percent frequency effect (IP), and radioelement content around a tin vein and stockwork deposit.

Adapted from Rulski, 1982.

Weethalle tin granite and surrounding area, New South Wales, Australia, flown at 85 m above ground and 250 m

line spacing. Adapted from Webster, 1984a.